


Cable glands > Brass > IP68 cable glands

Type: 2940.M50N

Family: 2940 M



MAXIBRASS CABLE GLAND, IN NICKEL-PLATED BRASS, WITH EXTENDED CLAMPING RANGE, M50X1,5, IP68

Technical info	
Range of operating temperature (static)	-40÷100 °C
Range of operating temperature (dynamic)	-25÷100 °C
Color	Nickel plated brass grey
Thread pitch	M50x1.5
Counter nut	No
External seal	Yes
Internal washers	No
Tightening torque	18 Nm
Range of length of total entry bush dimensions (L)	39÷48 mm

Weight and dimensions	
Spanner size for tightening the entry bush (B1)	57 mm
Spanner size for tightening the body (B2)	57 mm
Fixing hole diameter	50.5 mm
Width	61 mm
Length of the thread on the side of the insertion into the panel (C)	13 mm
Range of cable housing diameter	30÷38 mm

Material treatment and composition	
Body material	brass

Material treatment and composition	
Cage material	Polyamide PA6.6
Entry bush material	brass
Outer seal material	Nitrile 70 sh A
Inner seal material	Neoprene
Halogen free	No
Surface treatment	nickel plating
Minimum thickness surface coating	3 µm

Certifications and approvals	
Marks	CE; UKCA; VDE
Ingress Protection IP according to CEI EN 60529	IP66;IP68
Glow wire test	No
Reference standard	CEI EN 60423;CEI EN 62444
UL impact rating	6 IK
Type NEMA	1 (NEMA);;4X (NEMA);6P (NEMA)
Compliance according to CEI EN 62444	Yes

Logistics	
Minimum unit quantity	5
Standard unit quantity	5