

Type: DB250-11/1N



UNIPOLAR DISTRIBUTION BLOCK, DIRECT CLAMPING, 250A 12 WAYS SECTION 120mmq

Technical information	
Number of ways	11
Rated impulse voltage Uimp	1000 V
Rated peak withstand current IPK	51 kA
Rated short-time withstand current ICW	24.5 kA
Operating current	250 A
Input connection capacity	1x35÷120 mm² R/F
Output connection capacity	5x2.5÷16 mm² R/F; 4x2.5÷10 mm² R/F; 2x6÷35 mm² R/F
Number of poles	1
Clamping type	direct
Captive screw	Yes
Torque of the clamping element	35÷120 mm²: 19 Nm;2.5÷10 mm²: 2.7 Nm;2.5÷16 mm²: 2.7 Nm;6÷35 mm²: 4.4 Nm
Easy insertion input	Yes
Cover color	Transparent
Insulated body color	Grey
Attachment for DIN rail	Yes

Weight and dimensions	
Geometry of the clamping element	allen screw
Number and diameter of input holes	1x15 mm
Number and diameter of output holes	4x6.1 mm; 5x6.8 mm; 2x9 mm
Horizontal pitch between the sheet elements	1x15 mm

Material composition and treatments	
Conductor body material	brass
Insulated body material	Polyamide PA6.6
Cover material	Polycarbonate
Clamping element material	Zinc plated steel
Halogen free	Yes
Minimum thickness of the surface coating of the conducting body	3 µm
Surface treatment of the conductor body	electrolytic tin plating
Surface treatment of the clamping element	Zinc plating

Certifications and approvals	
Marks	CE; UKCA; UL (cURus)
REACH	Yes
ROHS	Yes
Reference standard	EN 60947-7-1
UL standard	1059
Self-extinguishing fire class according to UL 94	V0
Ingress Protection according to CEI EN 60529	IP20

Logistics	
Minimum packing unit	3
Standard packing unit	3