


Cable lugs > Pre-insulated > Cable terminals

Type: GF-F608

Family: F-F



FEMALE DISCONNECT TERMINAL, PRE-INSULATED WITH PC, YELLOW, FOR COPPER CODUCTORS, HALOGEN FREE, SECTION 4-6 MMQ

Technical information	
Maximum operating temperature	115 °C
Minimum operating temperature	-20 °C
Cable section range	4÷6 mm²
Colour of jacket	Yellow
Cable stripping length	7.2 mm
Presence of reinforcement ring	Yes
Easy entry	Yes
Anti-vibration	No
Type	single
Coupling type	Female
Insulation type	partial

Weight and dimensions	
Bow external diameter (Ø3)	8.1 mm
Barrel internal diameter (Ø)	4.8 mm
Bow internal diameter (Ø2)	6.6 mm
Tongue width	6.7 mm
Barrel length (A)	6.5 mm
Sleeve length (C)	14 mm
Tongue length	7.8 mm
Total connector length (L)	24.5 mm

Material composition and treatments	
Halogen-free	Yes
Insulating jacket material	Polycarbonate
Reinforcing ring material	Copper
Conductor body material	brass
Annealed	No

Certifications and approvals	
Marks	UL (cULus)
UL 94 self-extinguishing class	V0
Reference standards	CAN/CSA C22.2 No. 153-14;UL 310
REACH	Yes
ROHS	Yes

Logistics	
Minimum packaging unit	100
Standard packaging unit	1000