


Cable lugs > Pre-insulated > End sleeves

Type: PKD35016

Family: PKD



END SLEEVE, PRE-INSULATED WITH PA6, RED, FOR FLEXIBLE COPPER CONDUCTORS, SECTION 35MMQ P=16MM

Technical information	
Maximum operating temperature	105 °C
Minimum operating temperature	-20 °C
Cable section range	35±35 mm²
Colour of jacket	Red
Compatible cable class	5 class
Cable stripping length	16 mm
Easy entry	Yes
Dielectric strength of the insulating jacket	16.5 kV/mm
Type	single

Weight and dimensions	
Bow external diameter (Ø3)	13.5 mm
Bow internal diameter (Ø2)	12.7 mm
Tube external diameter (Ø3)	8.7 mm
Tube total length (L)	30 mm
Tube body length (P)	16 mm
Sleeve length (C)	14 mm

Material composition and treatments	
Halogen-free	Yes
Insulating jacket material	Polyamide
Conductor body material	Electrolytic copper with purity above 99,95%
Annealed	Yes

Certifications and approvals	
Marks	UL (cULus)
Reference standards	DIN 46228/4
REACH	Yes
ROHS	Yes

Logistics	
Minimum packaging unit	50
Standard packaging unit	300