


Cable lugs > Pre-insulated > End sleeves

Type: PKE1510

Family: PKE



END SLEEVE, PRE-INSULATED WITH PA6, BLACK, FOR FLEXIBLE COPPER CONDUCTORS, SECTION 1,5MMQ P=10MM

Technical information	
Maximum operating temperature	105 °C
Minimum operating temperature	-20 °C
Cable section range	1.5÷1.5 mm²
Colour of jacket	Black
Compatible cable class	5 class
Cable stripping length	10 mm
Easy entry	Yes
Dielectric strength of the insulating jacket	16.5 kV/mm
Type	single

Weight and dimensions	
Bow external diameter (Ø3)	4 mm
Bow internal diameter (Ø2)	3.5 mm
Tube external diameter (Ø3)	2 mm
Tube total length (L)	16 mm
Tube body length (P)	10 mm
Sleeve length (C)	6 mm

Material composition and treatments	
Halogen-free	Yes
Insulating jacket material	Polyamide
Conductor body material	Electrolytic copper with purity above 99,95%
Annealed	Yes

Certifications and approvals	
Marks	UL (cULus)
Reference standards	DIN 46228/4
REACH	Yes
ROHS	Yes

Logistics	
Minimum packaging unit	500
Standard packaging unit	5000